

Sentient SuiteTM System Control Panels



LED Lighting Control Panel

Housing

- NEMA 1 Enclosure
- Welded Construction

Outputs

- (4) CAT6
- (3)12VDC RGB LED Lighting Voltage
- (2) 20VDC Lighting Voltages
- (1) 20VDC Lighting Control Voltage
- (2) Fiber Optic / ST Connector
- (2) Audio (L/R)
- (2) HDMI Fiber Optic

Product Description

A wall mounted audio, video and electrical control system with internal circuitry and components for the audio and visual interior design system. The touchpad Sentient App wirelessly communicates with the System Control Panels.

Specifications

Electrical

• Voltage: 110 - 240 VAC

• FLA: 13A

• MCA: 30 Amps

• Phase: Single

• Frequency: 50/60 Hz

• Disconnect: Lockout/Tagout

• Emergency Power Delay: ~1sec.

• 2048 BTU/H

A/V Panel Dimensions

• 25"h x 22.25"w x 12.5"d (635mm x 562.5mm x 320mm)

• Weight: 66 lbs. (30Kg)

LED Lighting Panel Dimensions

• 24"h x 24"w x 10"d (610mm x 610mm x 254mm)

• Weight: 75 lbs. (34Kg)

Communication

POE Wireless Access Point

Installation

Wall Mount

One Year Limited Warranty

• Complete Component


Approval Listings

• cUL / ETL / CE




Circuit Diagram

(Refer to Project Specific Wiring Schematic)



Typical Installation






LED Lighting Panel Physical Properties

Note: The LED Lighting Control Panel requires 100-240VAC 50/60Hz 30A input circuit.

Dimensions: 24"h x 24"w x 10"d (610mm x 610mm x 254mm)

Weight: 75 lbs. (34Kg)



Audio/Video Control Panel Physical Properties

Note: The A/V Control Panel requires a grounded, 100-240VAC 50/60Hz 30A outlet.

Dimensions: 25"h x 22.25"w x 12.5"d (635mm x 562.5mm x 320mm)

Weight: 66 lbs. (30Kg)

